



1.5-PM1-A-F-C - Inverted Vent Check Valve PM1 Series 1.5?

Description

Prevents seawater from entering tanks
Allows air/vapor to escape when tank is filling
Allows air intake when tank is discharging
Inverted (gooseneck) design offers simplest means for your requirements
Design makes disassembly fast and easy

PRODUCT TYPE

1. simple

PRODUCT CAT

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Full Float

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPROXIMATE-WEIGHT-LB

1. 8

PA CLOSING-DEVICE-OPTION

1. Closing Device Innovative design is simple and cost effective

PA CONNECTION

1. Flanged

PA CONSTRUCTION



1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points Investment casting allows for higher accuracy and repeat ability during the casting process

PA DIMENSION-C-IN

1. '4

PA DIMENSION-D-IN

1. '4.75

PA DIMENSION-E-IN

1. '5

PA DIMENSION-F-IN

1. '1.5

PA DIMENSION-G-IN

1. '0.5

PA FLAME-INSECT-SCREEN

Hydrasearch 1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

PA FLOAT-OPTION

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

PA FLOW-RATE-AT-3-625-PSI-GPM

1. '56

PA HARDWARE

1. Stainless Steel

PA MATERIAL

1. Aluminum 535

PA MAX-INLET-AIR-SPEED-MPERS

1. '27

PA MINIMUM-ORDER

1. 1



PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

Hydrasearch

PA PACKAGE-TYPE

1. Each

PA PIPE-SIZE-A-IN

1. '1.5 In

PA STANDARD-SIZE-A-IN

1. '1.5

PA UNITS-PER-PACKAGE

1. 1

PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

Date

2025/07/30

Date Created

2024/03/23

Meta Fields

Tax Status: none Manage Stock: no Stock Status: instock

Sku: 1.5-PM1-A-F-C