



## 1.5-PM1-GS-T – Inverted Vent Check Valve PM1 Series 1.5?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Full Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 5

### PA CLOSING-DEVICE-OPTION

1. None (Standard)

### PA CONNECTION

1. Threaded

### PA CONSTRUCTION

1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points  
Investment casting allows for higher accuracy and repeat ability during the casting process

#### **PA DIMENSION-C-IN**

1. '4

#### **PA DIMENSION-D-IN**

1. '4.75

#### **PA DIMENSION-E-IN**

1. '5

#### **PA DIMENSION-F-IN**

1. '1.5

#### **PA DIMENSION-G-IN**

1. '0.5

#### **PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

#### **PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '56

#### **PA HARDWARE**

1. Stainless Steel

#### **PA MATERIAL**

1. Galvanized Steel

#### **PA MAX-INLET-AIR-SPEED-MPERS**

1. '27

#### **PA MINIMUM-ORDER**

1. 1

---

## PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

## PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

## PA PACKAGE-TYPE

1. Each

## PA PIPE-SIZE-A-IN

1. '1.5 In

## PA STANDARD-SIZE-A-IN

1. '1.5

## PA UNITS-PER-PACKAGE

1. 1

## PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

## Date

2025/08/14

## Date Created

2024/03/23

## Meta Fields

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 1.5-PM1-GS-T

Hydrasearch