



## 10-PM1-B-F – Inverted Vent Check (Half Float) 10?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Half Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. '127

### PA CLOSING-DEVICE-OPTION

1. None (Standard)

### PA CONNECTION

1. Flanged

### PA CONSTRUCTION

1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

**PA DIMENSION-C-IN**

1. '17

**PA DIMENSION-D-IN**

1. '13.25

**PA DIMENSION-E-IN**

1. '16

**PA DIMENSION-F-IN**

1. '4.25

**PA DIMENSION-G-IN**

1. '1

**PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

**PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

**PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '2000

**PA HARDWARE**

1. Stainless Steel

**PA MATERIAL**

1. Bronze B62

**PA MAX-INLET-AIR-SPEED-MPERS**

1. '9

**PA MINIMUM-ORDER**

1. 1

---

## PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

## PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

## PA PACKAGE-TYPE

1. Each

## PA PIPE-SIZE-A-IN

1. '10 In

## PA UNITS-PER-PACKAGE

1. 1

## PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

### Date

2025/08/11

### Date Created

2024/03/23

### Meta Fields

**Tax Status :** none      **Manage Stock :** no      **Stock Status :** instock

**Sku :**      10-PM1-B-F