



# 10-PM1-SS-W-P-C - Inverted Vent Check (Half Float) 10?

## Description

Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Inverted (gooseneck) design offers simplest means for your requirements Design makes disassembly fast and easy

## **PRODUCT TYPE**

1. simple

## **PRODUCT CAT**

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Half Float

## **PRODUCT SHIPPING CLASS**

1. Taxable Goods

## PA APPROXIMATE-WEIGHT-LB

1. '90

## PA CLOSING-DEVICE-OPTION

1. Closing Device Innovative design is simple and cost effective

## PA CONNECTION

1. Butt Weld

## PA CONSTRUCTION



1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

### **PA DIMENSION-C-IN**

1. '17

### **PA DIMENSION-D-IN**

1. '13.25

### **PA DIMENSION-E-IN**

1. '16

## **PA DIMENSION-F-IN**

1. '4.25

## **PA DIMENSION-G-IN**

### **PA FLAME-INSECT-SCREEN**

'1
A FLAME-INSECT-SCREEN
1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

## **PA FLOAT-OPTION**

1. Polyethylene

### PA FLOW-RATE-AT-3-625-PSI-GPM

1. '2000

#### **PA HARDWARE**

1. Stainless Steel

### **PA MATERIAL**

1. 316 Stainless Steel

#### PA MAX-INLET-AIR-SPEED-MPERS

1. '9

#### **PA MINIMUM-ORDER**

1. 1

#### **PA NITRILE-SEAL**



1. Maximize Low Pressure Sealing Oil And Fuel Resistant

#### **PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

#### **PA PACKAGE-TYPE**

1. Each

#### **PA PIPE-SIZE-A-IN**

1. '10 In

#### **PA UNITS-PER-PACKAGE**

1. 1

#### **PA VALVE-CAP**

1. Eliminates need for a spacer ring and protective screen

#### Date

I. Eliminal	es need for a spacer	ning and protective sc	ieen
<b>Date</b> 2025/07/26	Ŧ	The and protective sc	
<b>Date Created</b>			
2024/03/23			
Meta Fields			
Tax Status :	none	Manage Stock : no	Stock Status : instock
Sku :	10-PM1-SS-W-P-C		