



## 148-14504F – Firesleeves

### Description

In accordance with AS1072. Meets FAA TSO C53, TSO C75, and FAA TSO C42 standards. Silicone impregnated fiberglass braid provides increased service life under conditions of ambient temperatures -65°F to 450°F, intermittent to 500°F and is resistant to most aircraft fuels, oils and hydraulic fluids, including Skydrol 500 (a Monsanto trademark).

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Defense
2. Aerospace Hose & Fittings
3. Hose Protectants
4. Firesleeves

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA AS1072-SIZE

1. '09

### PA MAX-OD-IN

1. '0.90

### PA MIN-ID-IN

1. '0.52

### PA NOMINAL-ID

1. 0.56

**PA NOTES**

1. Dimensional Information Is For Reference Only. Variations From These Dimensions On Actual Parts May Occur As The Result Of Engineering Revisions.

**PA WEIGHT-LBS-PER-FT**

1. '0.16

**Date**

2024/11/22

**Date Created**

2024/03/22

**Meta Fields**

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 148-14504F

Hydrasearch