



# 2.5-PM1-A-F-P - Inverted Vent Check Valve PM1 Series 2.5?

# **Description**

Prevents seawater from entering tanks
Allows air/vapor to escape when tank is filling
Allows air intake when tank is discharging
Inverted (gooseneck) design offers simplest means for your requirements
Design makes disassembly fast and easy

### **PRODUCT TYPE**

1. simple

### **PRODUCT CAT**

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Full Float

#### PRODUCT SHIPPING CLASS

1. Taxable Goods

# PA APPROXIMATE-WEIGHT-LB

1. '17.5

# PA CLOSING-DEVICE-OPTION

1. None (Standard)

## **PA CONNECTION**

1. Flanged

#### PA CONSTRUCTION



1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points Investment casting allows for higher accuracy and repeat ability during the casting process

### PA DIMENSION-C-IN

1. '5.5

## PA DIMENSION-D-IN

1. '6.63

### PA DIMENSION-E-IN

1. '7

#### PA DIMENSION-F-IN

1. '1.88

### PA DIMENSION-G-IN

1. '0.5

# PA FLAME-INSECT-SCREEN

Hydrasearch 1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

### **PA FLOAT-OPTION**

1. Polyethylene

### PA FLOW-RATE-AT-3-625-PSI-GPM

1. '190

#### **PA HARDWARE**

Stainless Steel

### **PA MATERIAL**

1. Aluminum 535

# PA MAX-INLET-AIR-SPEED-MPERS

1. '26

## PA MINIMUM-ORDER

1. 1



### **PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

#### **PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

Hydrasearch

### PA PACKAGE-TYPE

1. Each

#### PA PIPE-SIZE-A-IN

1. '2.5 In

### PA STANDARD-SIZE-A-IN

1. '2.5

## PA UNITS-PER-PACKAGE

1. 1

# PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

**Date** 

2025/07/30

**Date Created** 

2024/03/23

**Meta Fields** 

Tax Status: none Manage Stock: no Stock Status: instock

**Sku**: 2.5-PM1-A-F-P