



## 2.5-PM1-A-T-P-C – Inverted Vent Check Valve PM1 Series 2.5?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Full Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 10.5

### PA CLOSING-DEVICE-OPTION

1. Closing Device Innovative design is simple and cost effective

### PA CONNECTION

1. Threaded

### PA CONSTRUCTION

1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points  
Investment casting allows for higher accuracy and repeat ability during the casting process

#### **PA DIMENSION-C-IN**

1. '5.5

#### **PA DIMENSION-D-IN**

1. '6.63

#### **PA DIMENSION-E-IN**

1. '7

#### **PA DIMENSION-F-IN**

1. '1.88

#### **PA DIMENSION-G-IN**

1. '0.5

#### **PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Polyethylene

#### **PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '190

#### **PA HARDWARE**

1. Stainless Steel

#### **PA MATERIAL**

1. Aluminum 535

#### **PA MAX-INLET-AIR-SPEED-MPERS**

1. '26

#### **PA MINIMUM-ORDER**

1. 1

---

## PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

## PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

## PA PACKAGE-TYPE

1. Each

## PA PIPE-SIZE-A-IN

1. '2.5 In

## PA STANDARD-SIZE-A-IN

1. '2.5

## PA UNITS-PER-PACKAGE

1. 1

## PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

### Date

2025/07/30

### Date Created

2024/03/23

### Meta Fields

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 2.5-PM1-A-T-P-C

Hydrasearch