



# 2.5-PM1-B-F – Inverted Vent Check Valve PM1 Series 2.5?

# Description

Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Inverted (gooseneck) design offers simplest means for your requirements Design makes disassembly fast and easy

## **PRODUCT TYPE**

1. simple

# **PRODUCT CAT**

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Full Float

### **PRODUCT SHIPPING CLASS**

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. '17.5

# PA CLOSING-DEVICE-OPTION

1. None (Standard)

# **PA CONNECTION**

1. Flanged

# PA CONSTRUCTION



1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points Investment casting allows for higher accuracy and repeat ability during the casting process

#### **PA DIMENSION-C-IN**

1. '5.5

#### **PA DIMENSION-D-IN**

1. '6.63

#### **PA DIMENSION-E-IN**

1. '7

#### **PA DIMENSION-F-IN**

1. '1.88

#### **PA DIMENSION-G-IN**

1. '0.5

### **PA FLAME-INSECT-SCREEN**

Hydrasearch 1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

#### PA FLOW-RATE-AT-3-625-PSI-GPM

1. '190

#### **PA HARDWARE**

1. Stainless Steel

#### **PA MATERIAL**

1. Bronze B62

#### **PA MAX-INLET-AIR-SPEED-MPERS**

1. '26

#### **PA MINIMUM-ORDER**

1. 1



#### **PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

#### **PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

Hydrasearch

#### **PA PACKAGE-TYPE**

1. Each

#### PA PIPE-SIZE-A-IN

1. '2.5 In

#### PA STANDARD-SIZE-A-IN

1. '2.5

#### **PA UNITS-PER-PACKAGE**

1. 1

### **PA VALVE-CAP**

1. Eliminates need for a spacer ring and protective screen

#### Date

2025/07/16 Date Created 2024/03/23 Meta Fields Tax Status : none Sku : 2.5-PM1-B-F