



## 2.5-PM1-GS-W-P – Inverted Vent Check Valve PM1 Series 2.5?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Full Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 10.5

### PA CLOSING-DEVICE-OPTION

1. None (Standard)

### PA CONNECTION

1. Butt Weld

### PA CONSTRUCTION

1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points  
Investment casting allows for higher accuracy and repeat ability during the casting process

**PA DIMENSION-C-IN**

1. '5.5

**PA DIMENSION-D-IN**

1. '6.63

**PA DIMENSION-E-IN**

1. '7

**PA DIMENSION-F-IN**

1. '1.88

**PA DIMENSION-G-IN**

1. '0.5

**PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

**PA FLOAT-OPTION**

1. Polyethylene

**PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '190

**PA HARDWARE**

1. Stainless Steel

**PA MATERIAL**

1. Galvanized Steel

**PA MAX-INLET-AIR-SPEED-MPERS**

1. '26

**PA MINIMUM-ORDER**

1. 1

**PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

**PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

**PA PACKAGE-TYPE**

1. Each

**PA PIPE-SIZE-A-IN**

1. '2.5 In

**PA STANDARD-SIZE-A-IN**

1. '2.5

**PA UNITS-PER-PACKAGE**

1. 1

**PA VALVE-CAP**

1. Eliminates need for a spacer ring and protective screen

**Date**

2024/12/22

**Date Created**

2024/03/23

**Meta Fields**

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 2.5-PM1-GS-W-P

Hydrasearch