



2-APH-GS-T-C-C – Cast Air Pipe Head 2?

Description

Prevents seawater from entering tanks

Allows air/vapor to escape when tank is filling

Allows air intake when tank is discharging

Vertical orientation is ideal for reducing weight and eliminates the need for a gooseneck pipe bend

PRODUCT TYPE

1. simple

PA CONNECTION

1. Threaded

PA CONSTRUCTION

1. Internal housing is removable for easy maintenance

PA DIMENSION-C-IN

1. '6

PA DIMENSION-D-IN

1. '7.5

PA DIMENSION-E-IN

1. '7.5

PA DIMENSION-F-IN

1. '4.5

PA DIMENSION-G-IN

1. '3

PA FLAME-INSECT-SCREEN

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

PA FLOAT-OPTION

1. Stainless Steel (Standard)

PA FLOW-RATE-AT-3-625-PSI-GPM

1. '150

PA HARDWARE

1. Stainless Steel

PA MATERIAL

1. Galvanized Steel

PA MAX-INLET-AIR-SPEED-MPERS

1. '36

PA MINIMUM-ORDER

1. 1

PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

PA PACKAGE-TYPE

1. Each

PA UNITS-PER-PACKAGE

1. 1

Date

2025/04/05

Date Created

2024/03/23

Meta Fields

Tax Status : none

Manage Stock : no **Stock Status :** instock

Sku : 2-APH-GS-T-C-C

Hydrasearch