



## 2-PM1-GS-T – Inverted Vent Check Valve PM1 Series 2?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Full Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 9

### PA CLOSING-DEVICE-OPTION

1. None (Standard)

### PA CONNECTION

1. Threaded

### PA CONSTRUCTION

1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points  
Investment casting allows for higher accuracy and repeat ability during the casting process

**PA DIMENSION-C-IN**

1. '5

**PA DIMENSION-D-IN**

1. '6.38

**PA DIMENSION-E-IN**

1. '6

**PA DIMENSION-F-IN**

1. '2

**PA DIMENSION-G-IN**

1. '0.5

**PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

**PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

**PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '95

**PA HARDWARE**

1. Stainless Steel

**PA MATERIAL**

1. Galvanized Steel

**PA MAX-INLET-AIR-SPEED-MPERS**

1. '42

**PA MINIMUM-ORDER**

1. 1

**PA NITRILE-SEAL**

- 1. Maximize Low Pressure Sealing Oil And Fuel Resistant

**PA NOTES**

- 1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

**PA PACKAGE-TYPE**

- 1. Each

**PA PIPE-SIZE-A-IN**

- 1. '2 In

**PA STANDARD-SIZE-A-IN**

- 1. '2

**PA UNITS-PER-PACKAGE**

- 1. 1

**PA VALVE-CAP**

- 1. Eliminates need for a spacer ring and protective screen

**Date**

2024/12/22

**Date Created**

2024/03/23

**Meta Fields**

**Tax Status :** none                      **Manage Stock :** no    **Stock Status :** instock

**Sku :**                      2-PM1-GS-T

