



3-PM1-A-S-P-C – Inverted Vent Check Valve PM1 Series 3?

## Description

Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Inverted (gooseneck) design offers simplest means for your requirements Design makes disassembly fast and easy

## **PRODUCT TYPE**

1. simple

## **PRODUCT CAT**

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Full Float

## **PRODUCT SHIPPING CLASS**

1. Taxable Goods

## PA APPROXIMATE-WEIGHT-LB

1. 15

## PA CLOSING-DEVICE-OPTION

1. Closing Device Innovative design is simple and cost effective

## PA CONNECTION

1. Socket Weld

# PA CONSTRUCTION



1. Four (4) guide ribs to assure proper sealing Recessed cap; eliminates catch points Investment casting allows for higher accuracy and repeat ability during the casting process

### **PA DIMENSION-C-IN**

1. '6.5

## **PA DIMENSION-D-IN**

1. '7.94

## **PA DIMENSION-E-IN**

1. '7.5

## **PA DIMENSION-F-IN**

1. '2

## **PA DIMENSION-G-IN**

1. '0.5

## **PA FLAME-INSECT-SCREEN**

Hydrasearch 1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Polyethylene

#### PA FLOW-RATE-AT-3-625-PSI-GPM

1. '205

#### **PA HARDWARE**

1. Stainless Steel

## **PA MATERIAL**

1. Aluminum 535

### PA MAX-INLET-AIR-SPEED-MPERS

1. '19

#### **PA MINIMUM-ORDER**

1. 1



#### **PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

#### **PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

Hydrasearch

### **PA PACKAGE-TYPE**

1. Each

#### PA PIPE-SIZE-A-IN

1. '3 In

#### PA STANDARD-SIZE-A-IN

1. '3

#### **PA UNITS-PER-PACKAGE**

1. 1

## **PA VALVE-CAP**

1. Eliminates need for a spacer ring and protective screen

#### Date

2025/06/28 Date Created 2024/03/23 Meta Fields Tax Status : none Sku : 3-PM1-A-S-P-C Manage Stock : no Stock Status : instock