



# 6-PM1-B-S-C - Inverted Vent Check (Half Float) 6?

# Description

Prevents seawater from entering tanks Allows air/vapor to escape when tank is filling Allows air intake when tank is discharging Inverted (gooseneck) design offers simplest means for your requirements Design makes disassembly fast and easy

### **PRODUCT TYPE**

1. simple

## **PRODUCT CAT**

- 1. Commercial & Recreational
- 2. Inverted Vent Check Valves
- 3. Inverted Vent Check Valves PM1 Series Half Float

### **PRODUCT SHIPPING CLASS**

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 35

# PA CLOSING-DEVICE-OPTION

1. Closing Device Innovative design is simple and cost effective

# PA CONNECTION

1. Socket Weld

# PA CONSTRUCTION



1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

#### **PA DIMENSION-C-IN**

1. '11.13

#### **PA DIMENSION-D-IN**

1. '9

#### **PA DIMENSION-E-IN**

1. '11

### **PA DIMENSION-F-IN**

1. '3.5

#### **PA DIMENSION-G-IN**

#### **PA FLAME-INSECT-SCREEN**

'1
 A FLAME-INSECT-SCREEN
 1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

#### PA FLOW-RATE-AT-3-625-PSI-GPM

1. '890

#### **PA HARDWARE**

1. Stainless Steel

#### **PA MATERIAL**

1. Bronze B62

#### PA MAX-INLET-AIR-SPEED-MPERS

1. '9

#### **PA MINIMUM-ORDER**

1. 1



#### **PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

#### **PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

#### **PA PACKAGE-TYPE**

1. Each

#### **PA PIPE-SIZE-A-IN**

1. '6 In

#### **PA UNITS-PER-PACKAGE**

1. 1

#### **PA VALVE-CAP**

A VALVE-CAP
1. Eliminates need for a spacer ring and protective screen

#### Date

2025/08/14				
<b>Date Created</b>				
2024/03/23				
Meta Fields				
Tax Status :	none	Manage Stock : no	Stock Status :	instock
Sku :	6-PM1-B-S-C			