



6-PM1-GS-F – Inverted Vent Check (Half Float) 6"

Description

Prevents seawater from entering tanks
Allows air/vapor to escape when tank is filling
Allows air intake when tank is discharging
Inverted (gooseneck) design offers simplest means for your requirements
Design makes disassembly fast and easy

PRODUCT TYPE

1. simple

PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Half Float

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPROXIMATE-WEIGHT-LB

1. '52

PA CLOSING-DEVICE-OPTION

1. None (Standard)

PA CONNECTION

1. Flanged

PA CONSTRUCTION

1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

PA DIMENSION-C-IN

1. '11.13

PA DIMENSION-D-IN

1. '9

PA DIMENSION-E-IN

1. '11

PA DIMENSION-F-IN

1. '3.5

PA DIMENSION-G-IN

1. '1

PA FLAME-INSECT-SCREEN

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

PA FLOAT-OPTION

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

PA FLOW-RATE-AT-3-625-PSI-GPM

1. '890

PA HARDWARE

1. Stainless Steel

PA MATERIAL

1. Galvanized Steel

PA MAX-INLET-AIR-SPEED-MPERS

1. '9

PA MINIMUM-ORDER

1. 1

PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

PA PACKAGE-TYPE

1. Each

PA PIPE-SIZE-A-IN

1. '6 In

PA UNITS-PER-PACKAGE

1. 1

PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

Date

2025/07/25

Date Created

2024/03/23

Meta Fields

Tax Status : none

Manage Stock : no **Stock Status :** instock

Sku : 6-PM1-GS-F