



## 6-PM1-SS-T – Inverted Vent Check (Half Float) 6?

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Half Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. 35

### PA CLOSING-DEVICE-OPTION

1. None (Standard)

### PA CONNECTION

1. Threaded

### PA CONSTRUCTION

1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

#### **PA DIMENSION-C-IN**

1. '11.13

#### **PA DIMENSION-D-IN**

1. '9

#### **PA DIMENSION-E-IN**

1. '11

#### **PA DIMENSION-F-IN**

1. '3.5

#### **PA DIMENSION-G-IN**

1. '1

#### **PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

#### **PA FLOAT-OPTION**

1. Stainless Steel (Standard) Full Round Seamless Polished Stainless Steel Float Assures A Positive Seal

#### **PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '890

#### **PA HARDWARE**

1. Stainless Steel

#### **PA MATERIAL**

1. 316 Stainless Steel

#### **PA MAX-INLET-AIR-SPEED-MPERS**

1. '9

#### **PA MINIMUM-ORDER**

1. 1

---

## PA NITRILE-SEAL

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

## PA NOTES

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

## PA PACKAGE-TYPE

1. Each

## PA PIPE-SIZE-A-IN

1. '6 In

## PA UNITS-PER-PACKAGE

1. 1

## PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

### Date

2025/07/30

### Date Created

2024/03/23

### Meta Fields

**Tax Status :** none      **Manage Stock :** no      **Stock Status :** instock

**Sku :** 6-PM1-SS-T