



6GN301 – Female Union x Female Union

Description

Basic valve configuration works with MIL-DTL-24578.
Working pressure is 6000 PSI.

PRODUCT TYPE

1. simple

PRODUCT CAT

1. Defense
2. Technical Products - Valves & Fittings
3. Valves Instrumentation & Adapters
4. Instrument Valves
5. Valve Instruments

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPLICATION

1. High Corrosion Resistant (Monel) - Hydraulic (System Fluid) High Corrosion Resistant (Monel) - Wog (System Fluid) Non-Magnetic (Stainless Steel) - Wog (System Fluid) Standard (Stain

PA BODY-TYPE

1. Inline

PA INLET-CONNECTION

1. '1/4" Npt Female

PA NOTES

1. Additional Configurations Are Available For Special Applications Please Contact Our Sales Department With Your Requirements.

PA OUTLET-CONNECTION

1. '1/4" Npt Female

PA REFERENCES

1. Technical Products Valves Instrumentation & Adapters Valve Information (Catalog 1220).Pdf

PA STEM-CONDITION

1. Vented

PA TYPE-1

1. Needle

PA WORKING-PRESSURE-PSI

1. '6

Date

2025/07/25

Date Created

2024/03/22

Meta Fields

Tax Status : none **Manage Stock :** no **Stock Status :** instock

Sku : 6GN301

Hydrasearch