



## 8-PM1-GS-T-P – Inverted Vent Check (Half Float) 8"

### Description

Prevents seawater from entering tanks  
Allows air/vapor to escape when tank is filling  
Allows air intake when tank is discharging  
Inverted (gooseneck) design offers simplest means for your requirements  
Design makes disassembly fast and easy

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Inverted Vent Check Valves
3. Inverted Vent Check Valves PM1 Series - Half Float

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA APPROXIMATE-WEIGHT-LB

1. '54

### PA CONNECTION

1. Threaded

### PA CONSTRUCTION

1. Four (4) Guide Ribs To Assure Proper Sealing Recessed Cap; Eliminates Catch Points

### PA DIMENSION-C-IN

1. '14.13

**PA DIMENSION-D-IN**

1. '10.75

**PA DIMENSION-E-IN**

1. '13.5

**PA DIMENSION-F-IN**

1. '3.5

**PA DIMENSION-G-IN**

1. '1

**PA FLAME-INSECT-SCREEN**

1. Corrosion Resistant For Ignition Protection Easily Accessible For Maintenance

**PA FLOAT-OPTION**

1. Polyethylene

**PA FLOW-RATE-AT-3-625-PSI-GPM**

1. '1520

**PA HARDWARE**

1. Stainless Steel

**PA MATERIAL**

1. Galvanized Steel

**PA MAX-INLET-AIR-SPEED-MPERS**

1. '8

**PA MINIMUM-ORDER**

1. 1

**PA NITRILE-SEAL**

1. Maximize Low Pressure Sealing Oil And Fuel Resistant

**PA NOTES**

1. Air Intake Tested With Polyethylene Float (Lightest Float) And The Water Pumped Through The Vent Check Valves For The Flow Rate.

#### PA PACKAGE-TYPE

1. Each

#### PA PIPE-SIZE-A-IN

1. '8 In

#### PA UNITS-PER-PACKAGE

1. 1

#### PA VALVE-CAP

1. Eliminates need for a spacer ring and protective screen

#### Date

2025/05/02

#### Date Created

2024/03/23

#### Meta Fields

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 8-PM1-GS-T-P