



88B0100008F0000 – High Pressure Rubber Hose Assemblies

Description

Hydrasearch MS28759, flared, high pressure hose assemblies can be used as flexible connections on high pressure power plant and airframe applications (see SAE-AIR797). They are especially suited for high pressure hydraulic fluids, engine oils, fuels and coolant fluids. Hydrasearch high pressure hose is used for applications with operating pressures to 3000 PSI, and having a temperature range of -65°F to +275°F (see MIL-DTL-8788 for specific temperature ranges).

PRODUCT TYPE

1. simple

PRODUCT CAT

1. Defense
2. Aerospace Hose & Fittings
3. Hose Assemblies
4. High Pressure Rubber Hose Assemblies

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA FINISH

1. Aluminum Alloy

PA FITTING-MIL-SPEC

1. Mil-Dtl-8789

PA HOSE-ASSEMBLY-MIL-SPEC

1. Mil-Dtl-8790

PA HOSE-ID-IN

- 1. '0.438

PA HOSE-MIL-SPEC

- 1. Mil-Dtl-8788

PA HOSE-SIZE-IN

- 1. '1/2

PA MATERIAL

- 1. Aluminum And Steel In Accordance With Table I Of Mil-Dtl-8789.All Sizes Are Steel With Aluminum Sockets.

PA MAX-OPERATING-PRESSURE-PSI

- 1. '3

PA MS-PART-NO

- 1. Ms28759-8L

PA NOTES

- 1. Dimensional Information Is For Reference Only. Variations From These Dimensions On Actual Parts May Occur As The Result Of Engineering Revisions.

PA SIZE-IN

- 1. '-08

PA THREAD-SIZE-T

- 1. 3/4"-16

Date

2024/11/24

Date Created

2024/03/22

Meta Fields

Tax Status : none

Manage Stock : no **Stock Status :** instock

Sku : 88B0100008F0000