



## 88B0100016F0000 – High Pressure Rubber Hose Assemblies

### Description

Hydrasearch MS28759, flared, high pressure hose assemblies can be used as flexible connections on high pressure power plant and airframe applications (see SAE-AIR797). They are especially suited for high pressure hydraulic fluids, engine oils, fuels and coolant fluids. Hydrasearch high pressure hose is used for applications with operating pressures to 3000 PSI, and having a temperature range of -65°F to +275°F (see MIL-DTL-8788 for specific temperature ranges).

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Defense
2. Aerospace Hose & Fittings
3. Hose Assemblies
4. High Pressure Rubber Hose Assemblies

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA FINISH

1. Aluminum Alloy

### PA FITTING-MIL-SPEC

1. Mil-Dtl-8789

### PA HOSE-ASSEMBLY-MIL-SPEC

1. Mil-Dtl-8790

---

**PA HOSE-ID-IN**

- 1. '0.875

**PA HOSE-MIL-SPEC**

- 1. Mil-Dtl-8788

**PA HOSE-SIZE-IN**

- 1. '1

**PA MATERIAL**

- 1. Aluminum And Steel In Accordance With Table I Of Mil-Dtl-8789.All Sizes Are Steel With Aluminum Sockets.

**PA MAX-OPERATING-PRESSURE-PSI**

- 1. '3

**PA MS-PART-NO**

- 1. Ms28759-16L

**PA NOTES**

- 1. Dimensional Information Is For Reference Only. Variations From These Dimensions On Actual Parts May Occur As The Result Of Engineering Revisions.

**PA SIZE-IN**

- 1. '-16

**PA THREAD-SIZE-T**

- 1. 1-5/16"-12

**Date**

2025/07/31

**Date Created**

2024/03/22

**Meta Fields**

**Tax Status :** none

**Manage Stock :** no **Stock Status :** instock

**Sku :** 88B0100016F0000