



## G-138-312 – 1-3/8" Lasdrop Shaft Seal

### Description

- 1 3/8" Shaft, 3 1/2" Stern tube, Single water injection
- The Gen II uses a 316-marine grade stainless steel spring to provide pressure to the seal surfaces. Together, the spring and seal ring rotate along with the shaft, and remain secured in the Clamp/Pressure housing.
- The Clamp/Pressure housing is secured to the shaft without the use of set screws preventing galling or damage to the shaft.
- Dual u-cup seals rotate on the shaft and are seated inside of the seal ring to prevent the passage of water to this point.

### PRODUCT TYPE

1. simple

### PRODUCT CAT

1. Commercial & Recreational
2. Drivetrain
3. Packing Boxes
4. Lasdrop Shaft Seals

### PRODUCT SHIPPING CLASS

1. Taxable Goods

### PA PACKAGE-TYPE

1. Each

### PA SHAFT-SIZE-IN

1. '1-3/8

**PA STERN-TUBE-OD-IN**

1. '3-1/2

**PA UNITS-PER-PACKAGE**

1. 1

**Date**

2024/10/06

**Date Created**

2024/03/22

**Meta Fields**

**Tax Status :** none      **Manage Stock :** no      **Stock Status :** instock

**Sku :**      G-138-312

Hydrasearch