



HS133-06 - HS133 Series - High Pressure Hoses

Description

MIL-DTL-24136/2

Equal to Aeroquip P/N FC133

Use with Hydrasearch HS1489 Series Fittings:

Materials: Synthetic rubber tube and cover reinforced with synthetic fiber.

Application: Fresh and salt water systems, hydraulic systems, fuel systems, oil applications and low pressure air.

Operating Temperature Range: -40°F to +200°F

PRODUCT TYPE

1. simple

PRODUCT CAT

- 1. Defense
- 2. Marine Hose & Fittings
- 3. Marine Hose and Assemblies
- 4. HS133 Series High Pressure Hoses

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPLICABLE-FITTINGS

1. Hs1489

PA APPLICATION



Fresh And Salt Water Systems

PA BURST-PRESSURE-PSI

1. '8

PA CONSTRUCTION-REINFORCEMENT

1. Braided

PA EQUAL-TO-AEROQUIP-NO

1. Fc133-06

PA HOSE-ID-IN

1. '3/8

PA HOSE-SIZE-DASH-NO

1. '-6

Hydrasearch PA HYDRASEARCH-DRAWING-NO

1. C18443-1

PA LAYERS-REINFORCEMENT

1. '3

PA MATERIAL

1. Synthetic Rubber Tube And Cover Reinforced With Synthetic Fiber

PA MAX-DIMENSION-A-IN

1. '0.390

PA MAX-DIMENSION-B-IN

1. '1.031

PA MIL-SPEC

1. Mil-Dtl-24136/2

PA MIN-BEND-RADIUS-IN

1. '5.00

PA MIN-DIMENSION-A-IN



1. '0.359

PA MIN-DIMENSION-B-IN

1. '0.968

PANSN-NO

1. 4720-01-021-1586

PA WEIGHT-PER-FT-LBS

1. '0.46

PA WORKING-PRESSURE-PSI

1. '2

Date 2025/07/15 **Date Created** 2024/03/22 **Meta Fields**

Manage Stock: no Stock Status: instock Tax Status: none

Sku: HS133-06