



HS133-20 – HS133 Series – High Pressure Hoses

Description

MIL-DTL-24136/2

Equal to Aeroquip P/N FC133

Use with Hydrasearch HS1489 Series Fittings.

Materials: Synthetic rubber tube and cover reinforced with synthetic fiber.

Application: Fresh and salt water systems, hydraulic systems, fuel systems, oil applications and low pressure air.

Operating Temperature Range: -40°F to +200°F

PRODUCT TYPE

1. simple

PRODUCT CAT

1. Defense
2. Marine Hose & Fittings
3. Marine Hose and Assemblies
4. HS133 Series - High Pressure Hoses

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPLICABLE-FITTINGS

1. Hs1489

PA APPLICATION

1. Fresh And Salt Water Systems

PA BURST-PRESSURE-PSI

1. 4

PA CONSTRUCTION-REINFORCEMENT

1. Braided

PA EQUAL-TO-AEROQUIP-NO

1. Fc133-20

PA HOSE-ID-IN

1. '1-1/4

PA HOSE-SIZE-DASH-NO

1. '-20

PA HYDRASEARCH-DRAWING-NO

1. C18443-5

PA LAYERS-REINFORCEMENT

1. '3

PA MATERIAL

1. Synthetic Rubber Tube And Cover Reinforced With Synthetic Fiber

PA MAX-DIMENSION-A-IN

1. '1.289

PA MAX-DIMENSION-B-IN

1. '2.069

PA MIL-SPEC

1. Mil-Dtl-24136/2

PA MIN-BEND-RADIUS-IN

1. '16.00

PA MIN-DIMENSION-A-IN

1. '1.211

PA MIN-DIMENSION-B-IN

1. '1.975

PA NSN-NO

1. 4720-00-167-4726

PA WEIGHT-PER-FT-LBS

1. '1.26

PA WORKING-PRESSURE-PSI

1. '1

Date

2024/10/01

Date Created

2024/03/22

Meta Fields

Tax Status : none

Manage Stock : no **Stock Status :** instock

Sku : HS133-20

