



HSSA-24 – HSSA Series – Super Aquaduct Layflat Hoses

Description

Use with Hydrasearch LFS Elbows and End Fittings.

For a complete line of fittings and accessories see *Hydrasearch Layflat & Rubber Hose Catalog*.

Materials: Polyurethane elastomer tube and cover reinforced with high tenacity polyester.

Application: Salt and fresh water conveying systems.

Operating Temperature Range: -40°F to +200°F

PRODUCT TYPE

1. simple

PRODUCT CAT

1. Defense
2. Marine Hose & Fittings
3. Marine Hose and Assemblies
4. HSSA Series - Super Aquaduct Layflat Hoses

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPLICABLE-FITTINGS

1. Lfs Elbows And End Fittings

PA APPLICATION

1. Salt And Fresh Water Conveying Systems

PA BURST-PRESSURE-PSI

1. 600

PA CONSTRUCTION-REINFORCEMENT

1. Polyester

PA HOSE-ID-IN

1. '1-1/2

PA HOSE-SIZE-DASH-NO

1. '-24

PA HYDRASEARCH-DRAWING-NO

1. '18283

PA LAYERS-REINFORCEMENT

1. '1

PA MATERIAL

1. Polyurethane Elastomer Tube And Cover Reinforced With High Tenacity Polyester

PA MAX-DIMENSION-A-IN

1. '1.59

PA MAX-DIMENSION-B-IN

1. '1.73

PA MIN-DIMENSION-A-IN

1. '1-1/2

PA MIN-DIMENSION-B-IN

1. '1.64

PA WEIGHT-PER-FT-LBS

1. '0.144

PA WORKING-PRESSURE-PSI

1. '300

Date

2024/11/25

Date Created

2024/03/22

Meta Fields

Tax Status : none **Manage Stock :** no **Stock Status :** instock

Sku : HSSA-24

Hydrasearch