



HSSA-48 - HSSA Series - Super Aquaduct Layflat Hoses

Description

Use with Hydrasearch LFS Elbows and End Fittings.

For a complete line of fittings and accessories see *Hydrasearch Layflat & Rubber Hose Catalog*.

Materials: Polyurethane elastomer tube and cover reinforced with high tenacity polyester.

Application: Salt and fresh water conveying systems.

Operating Temperature Range: -40°F to +200°F

PRODUCT CAT

- 1. Defense
- 2. Marine Hose & Fittings
- 3. Marine Hose and Assemblies
- 4. HSSA Series Super Aquaduct Layflat Hoses

PRODUCT SHIPPING CLASS

1. Taxable Goods

PA APPLICABLE-FITTINGS

1. Lfs Elbows And End Fittings

PA BURST-PRESSURE-PSI

1.600

PA CONSTRUCTION-REINFORCEMENT

1. Polyester



PA HOSE-SIZE-DASH-NO

1. -48

PA HYDRASEARCH-DRAWING-NO

1. '18284

PA LAYERS-REINFORCEMENT

1. '1

PA MAX-DIMENSION-A-IN

1. '3.06

PA MAX-DIMENSION-B-IN

1. '3.24

PA MIN-DIMENSION-A-IN

1. '2.97

PA MIN-DIMENSION-B-IN

1. '3.15

PA WEIGHT-PER-FT-LBS

1. '0.342

PA WORKING-PRESSURE-PSI

1. '300

Date

2024/10/05

Date Created

2024/03/22

Meta Fields

Tax Status: none Manage Stock: no Stock Status: instock

Sku: HSSA-48

