



# Motor Assembly: Ice Eater 47511/250/615

# Description

#### **Replacement Motor Assembly**

An Ice Eater Replacement Motor Assembly is the perfect option to buy when you already have a shroud from an older or broken Ice Eater.

# The Motor Assembly comes with Motor Canister, Aluminum Anode, Propeller, Brackets, and Power Cord.

However, the Shroud, Mooring Lines, & Shackles are not included.

MODEL P250 SPECIFICATIONS:

- .25 Horse Power
- 2.6 Amps (115V) / 1.3 Amps (230V)
- Open Diameter: 20 (Open Diameter based on normal winter conditions)
- Gallons per Minute: 360

MODEL P500 SPECIFICATIONS:

This option works perfectly to replace .33 Horse Power units.

- .50 Horse Power
- 6.0 Amps (115V) / 3.0 Amps (230V)
- Open Diameter: 40? (Open Diameter based on normal winter conditions)
- Lbs of Thrust: 32
- Gallons per Minute: 1075

MODEL P750 SPECIFICATIONS:

- .75 Horse Power
- 6.0 Amps (115V) / 3.0 Amps (230V)



- Open Diameter: 60? (Open Diameter based on normal winter conditions)
- Lbs of Thrust: 34
- Gallons per Minute: 1250

MODEL P1000 SPECIFICATIONS:

- 1.0 Horse Power
- 7.4 Amps (115V) / 3.7 Amps (230V)
- Open Diameter: 80? (Open Diameter based on normal winter conditions)
- Lbs of Thrust: 36
- Gallons per Minute: 1400

The Ice Eater is designed to prevent ice from forming around boats, marinas, docks, and piers as well as effectively melting existing ice by breaking the surface with a continuous current of warmer bottom water.

The Ice Eater's propeller draws up warmer subsurface water and deflects it to the surface creating a constant circulation of warmer water that prevents ice formation and melts existing ice. Unlike other de-icing units, the Ice Eater requires no additional hardware in order to obtain the desired deicing pattern. Hydrasearch

# **PRODUCT TYPE**

1. simple

## PRODUCT CAT

Ice Eater Parts and Accessories

## PA CORD

1. 250'

#### **PA GALLONS-PER-MINUTE-GPM**

1. 360

## PA HP-HP

1. 0.75

#### **PA VOLTS**

1. 230V

#### Date

2025/07/16 Date Created 2024/08/16 Meta Fields Tax Status : none Manage Stock : no Stock Status : instock



**Sku :** 47511.250.615

Hydrasearch