



OLYMPUS REPLACEMENT POWER CORD: 230V, 200? length (600V; 10/4; STOW; cUL E226104) with Bulgin Female connection

# **Description**

Replacement SJTOW Power Cords for your Ice Eaters, F-Series Aeration Equipment, and Jydrasearc' **Decorative Lighting.** 

**Product Specifications** 

SJTOW UL & CSA Approved – Underwater Rated 3-Wire Cable **Potted Quick Disconnect** 115V NEMA 5-15P Plug | 230V NEMA 6-15P Plug

Please refer to the Ordering Guide for assistance.

**Ordering Guide** 

## **16/3 GAUGE WIRE**

- Available for Ice Eaters and Decorative Lighting
- The Quick Disconnect Connector has an Outside Diameter of 1 1/8?
- 115V / 230V Available Up to 100? Long

### 14/3 GAUGE WIRE



- Available for Ice Eaters, F-Series (12/3 Gauge Predominantly Used between May 2017 - May 2019), and Decorative Lighting
- The Quick Disconnect Connector has an Outside Diameter of 1 1/8?
- 115V Available Up to 150? Long / 230V Available Up to 400? Long

### 12/3 GAUGE WIRE

- Available for F-Series Equipment Predominantly Used Between May 2017 May 2019
- o The Quick Disconnect Connector has an Outside Diameter of 1 3/8?
- ydrasear 115V Available Up to 150? Long / 230V Available Up to 350? Long

#### **Install Instructions**

- 1. Unplug the Unit From the Power Source
- 1. Loosen and Remove the Existing Power Cord
- 1. Take Replacement Power Cord and Run Through the 2-1/2? Water Intake Hole at the Bottom of the Shroud
- 1. Apply a Small Pea-Sized Amount of Dielectric Grease to Power Cord Connector



1. Line Up the Pins and Holes From the Power Cord and Connector on the End Bell, and Then Twist it on

Make Sure to Hand Tighten Only - Do Not Over Tighten - Do Not Use Tools

- 1. In Order to Prevent the Power Cord from Hitting the Propeller, Pull Out Additional Slack Through the 2 1/2? Water Intake Hole and Secure with Clip and Screw One Additional measure you can take is to secure the power cord to a bracket with a zip tie and then secure with the clip and screw on the shroud.
- 1. Spin the propeller by hand after you complete the install to make sure the propeller does not hit the cord.

Hydrasearch

**Date**2025/06/17 **Date Created**2024/10/28 **Meta Fields** 

Tax Status: none Manage Stock: no Stock Status: instock

**Sku:** 104.200.615